

雙面研磨機 / 拋光機



單位：mm

規格 \ 型式	4B	6B	9B	12B	Model	Specifications
研磨盤直徑	265 φ × 114 φ × 16T	374 φ × 150 φ × 20T	630 φ × 245 φ × 30T	753 φ × 260 φ × 40T		Diameter of lapping plate
最大加工直徑	70 φ	110 φ	180 φ	220 φ		Maximum diameter of products
夾具直徑	99.6 φ (PCD)	139.3 φ (PCD)	228.5 φ (PCD)	283.6 φ (PCD)		Diameter of carrier (PCD)
夾具數量	5 枚	5 枚	5 枚	5 枚		Number of carriers
最小厚度	30 μ	80 μ	300 μ	300 μ		Minimum thickness of products
下盤轉速	0 ~ 60 RPM	0 ~ 60 RPM	0 ~ 60 RPM	0 ~ 60 RPM		Rotating speed of lower lapping plate (PRM)
反轉機構	CW & CCW	CW & CCW	CW & CCW	CW & CCW		Reversal mechanism of carrier
研磨主馬力	0.75KW	1.5KW	3.7KW	5.5KW		Main motor of lapping
拋光主馬力	1.5KW	2.2KW	5.5KW	7.5KW		Main motor of polishing
尺寸	830×600×1700	930×700×1930	1480×880×2400	1610×1200×2400		Size
重量	600KGS	800KGS	1800KGS	2600KGS		Weight